

## Flexa

Dante Bonuccelli

### Technical features

Armchair for conference halls, auditoriums, lecture rooms and multipurpose spaces.

### Typologies

Armchairs with floor-length sides. Installation on horizontal and sloped flooring or on steps, in straight or curved rows (on project). Centre to centre distance from 53 to 60 cm.

### Seat and backrest

Seat with internal structure in plywood. Fire-retardant crushproof expanded polyurethane padding.

Tip-up seat with gravity counterweight system, equipped with rotation pins and double steel support plate fixed to the inner structure. Rubber shock absorbers allow tilting with a controlled and silent movement.

The seat, completely upholstered and removable, can be equipped in the lower part with a visible painted wood panel in beech or oak finishes. Covering in fabric, faux-leather or leather.

Backrest composed of a load-bearing visible backrest panel and an inner backrest panel in plywood, with ergonomically shaped padding for correct lumbar support in fire-retardant crushproof expanded polyurethane padding. Upholstery in fabric, leather or faux-leather. The backrest panel in curved plywood is available with a visible painted wood, oak and beech finishes, or fully upholstered.

A folding table with anti-panic movement equipped with slow and cushioned closing (Patent Pending) can be applied to the rear of the backrest, which guarantees a controlled, safe and silent transition from the position of use to that of rest. CertiPUR® certified padding. Wooden components with low formaldehyde emissions.

### Sides

Load-bearing side with internal plywood structure equipped with metal inserts, available fully upholstered and covered in fabric, faux-leather or leather, or in painted wood version with beech or oak finishes. Wooden components with low formaldehyde emission, compliant with the new European limits. Sides can be equipped with tip-up writing tablet and foldaway anti-panic movement made with a large black stratified HPL top and die-cast aluminum joint.

Floor anchoring feet in steel profile with epoxy-polyester powder coating with scratch-resistant finish.

### Accessories

Tip-up foldaway writing tablet in stratified HPL.

Provision for electrification on the side (socket on demand)

Backrest tip-up writing tablet with anti-panic movement, slow and cushioned closing (Patent Pending), HPL bilaminate top in oak, beech or black finishes

Provision for electrification on the backrest (socket on demand)

Nameplate

Row identification and seat numbering element.

Painted wood backrest panel in oak or beech finishes.

Tip-up writing tablet on single- base mod T200.

Tested according to European standards